



LBB 3222/04 Interpreter Desk



- ▶ Accommodates 6 different language channels plus the original floor language
- ▶ Incoming channel pre-selector key eliminates the need to manually search through all available language channels
- ▶ Quick switching between the floor language and the channel set on the channel selector reduces the chance of operator errors
- ▶ Electronic channel interlock function prevents interpreters in different booths from using the same output channel

Functions

- Built-in loudspeaker
- 12 interpreter desks can be loop-through connected within and/or between interpreter booths
- Up to three interpreter desks can be present per booth
- Auto relay enable function allows the interpreter to provide the auto relay language (OR2) for relay interpretation
- The channel B disable function allows the interpreter to disable channel B while ensuring that the desk remains connected to channel A

Controls and Indicators

- Microphone mounted on a flexible stem, complete with a light ring which illuminates when the microphone is on
- Headphone volume, treble and bass controls
- A-B channel selector key with channel select indicators
- Six outgoing B-channel select keys with channel select indicators
- Outgoing 'OR2' (auto relay) indicator
- 'Channel engaged' indicators to show which channels are in use by other interpreters
- Microphone 'mute' key
- Microphone activating key with LED status indicator
- Select key with LED indicators for fast switching between the original floor language and the channel set on the channel selector

- Incoming channel 'OR2' (auto relay) indicator to show that the original floor language has been replaced by a transfer interpretation channel, when the auto-relay facility is in operation
- Incoming language channel selector for headphone monitoring
- Call key (voice) to provide two-way communication between interpreter and chairman/operator
- Outgoing message key
- Incoming message indicator
- Rotary switch to preset the outgoing channel via the A output

Interconnections

- 3 m (10 ft) cable terminated with a 25-pin sub D-type connector
- 25-pin sub D-type socket for loop-through connections
- 6.3 mm (0.25 in) stereo jack headphone connectors
- 15-pole 180° DIN-type socket for connection of interpreter's headset with microphone, plus switch to mute the built-in microphone
- Auxiliary socket (message) for the desk's message function

Technical Specifications

Electrical

Frequency response 125 Hz (-10 dB) to 12.5 kHz (-2 dB)

Rated equivalent sound pressure due to inherent noise < 32 dB

Total harmonic distortion at overload < 5%

Crosstalk attenuation > 66 dB

Mechanical

Mounting tabletop or flush mounting

Dimensions (H x W x D) 20-58 x 250 x 189 mm
(0.79-2.28 x 9.84 x 7.44 in)

Weight 1.75 kg (3.85 lb)

Color light grey

Ordering Information

LBB 3222/04 Interpreter Desk

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by