

DCN-WDDCS-D Wireless Discussion Unit with Dual Channel Selector

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Used as (dual) delegate or chairman unit
- ▶ Dual channel selector with number and abbreviated channel name
- ▶ Separate battery pack, easy to change and charge
- ▶ Advanced power saving techniques
- ▶ Low susceptibility to electromagnetic interference

To the participant the most important part of a conference system is the discussion unit. Bosch has built on the elegant design of the DCN Nex Generation discussion units to create a new series of wireless discussion units with unrivalled looks and features. The DCN-WDDCS-D Wireless Discussion Unit with Dual Channel selector enables participants to speak, register a request-to-speak, listen to the speaker or to an interpreter of their choice.

Functions

Speech intelligibility

Maximum speech intelligibility is guaranteed at all times. Operating in the 2.4 GHz (license free) band, the wireless discussion units produce crystal-clear sound due to a very high signal-to-noise ratio and antenna diversity. This means the signal is transmitted along different propagation paths, ensuring optimal receipt. The system is also protected against interference from mobile phones and other equipment that makes use of Bluetooth or microwave signals.

Security

Wireless communication means extra security considerations. The DCN Wireless system and discussion units therefore feature 128-bits AES encryption to prevent eavesdropping and unauthorized access. Encryption ensures the information within the system remains confidential.

Channel selector

The unit has two built-in channel selectors that makes it suitable for discussions in which more than one language is used, and simultaneous interpretations are available. The channel selector includes two up-and-down channel select keys, and a display showing the number and the abbreviation of the languages. This enables rapid selection of the required language channel.

Microphones

A socket is provided to connect the pluggable microphones which are available in short and long stem versions (DCN-MICS and DCN-MICL, to be ordered separately).

Headphones and loudspeakers

The unit also accommodates two headphone connections, so the speaker can be heard clearly even with excessive background noise. To prevent acoustic feedback the built-in loudspeaker is muted when the microphone is on. If enabled, the headphone volume is also automatically reduced to prevent acoustic feedback when the microphone is on.

Rims and buttons

Different rims are available to allow matching with the interior (DCN-DISR, to be ordered separately).

The unit can be used as:

- a single delegate unit
- a dual delegate unit
- a chairman unit (DCN-DISBCM chairman buttons, to be ordered separately)
- a single delegate unit with auxiliary button (to be used as an usher call, for example).

Battery maintenance

Simple battery maintenance is essential in a wireless system. A unique feature of Bosch's wireless discussion units is the separate rechargeable battery packs (DCNW-LIION, to be ordered separately). These Lithium-ion battery packs can be removed and replaced in a matter of seconds, providing maximum flexibility in recharge scheduling.

Controls and Indicators

On front

- Two alphanumeric displays for language channel selection with number and abbreviated channel name
- Two individual channel up and down selection buttons
- Two individual microphone buttons with a red or green illuminated ring:
 - Red indicates microphone is active
 - green indicates request-to-speak accepted*
- Two individual headphone volume control buttons

On rear

- Out-of-range indicator
- Battery low indicator

Under base

- Recessed 'De-init' switch
- Mode select switches (delegate, chairman, etc.)

Interconnections

- Socket for pluggable microphone
- Two 3.5 mm (0.14 in) headphone sockets stereo jack type
- DC power input from DCN-WPS (accessible when battery pack is removed)

* When unit is used in Dual Delegate mode, this function is available individually.

Technical specifications

Electrical

Frequency response	30 Hz - 20 kHz
Headphone load impedance	>32 ohm <1k ohm
Output power	2 x 15 mW/32 ohm

Mechanical

Mounting	Tabletop
Dimensions (H x W x D)	
without microphone	61 x 190 x 160 mm (2.4 x 7.5 x 6.3 in)
Weight	
without battery	515 g (1.14 lb)
with battery	730 g (1.61 lb)
Color top	Silver (RAL 9022)
Color base	Charcoal (PH 10736)

Ordering information

DCN-WDDCS-D Wireless Discussion Unit with Dual Channel Selector

pluggable microphone, dark base; microphone, rims and batteries to be ordered separately
Order number **DCN-WDDCS-D**

DCN-MICS Pluggable Short Microphone

length 310 mm (12.2 inch), silver
Order number **DCN-MICS**

DCN-MICL Pluggable Long Microphone

length 480 mm (18.9 inch), silver
Order number **DCN-MICL**

DCN-DISRH-SR Rim High Gloss Silver (10 pcs)

silver, high gloss, 10 pieces
Order number **DCN-DISRH-SR**

DCN-DISR-SR Rim Silver (10 pcs)

silver, 10 pieces
Order number **DCN-DISR-SR**

DCN-DISR-D Rim Dark (10 pcs)

dark, 10 pieces
Order number **DCN-DISR-D**

DCN-DISRMH Rim Metal High Gloss (10 pcs)

metal, high gloss, 10 pieces
Order number **DCN-DISRMH**

DCN-DISRMS Rim Metal Semi Gloss (10 pcs)

metal, semi gloss, 10 pieces
Order number **DCN-DISRMS**

Certifications and approvals

Region	Certification
Europe	CE

DCN-DISBCM Buttons Chairman (10 sets)

10 sets

Order number **DCN-DISBCM**

DCN-WLIION-D Battery Pack for Wireless Discussion Units

charcoal color, lithium-ion, 7.2 VDC, 4800 mAh

Order number **DCN-WLIION-D**

DCN-WPS Power Supply for Wireless Discussion Units

not approved for some countries

Order number **DCN-WPS**

DCN-FCWD10 Flight Case for 10 Wireless Discussion Units

light grey, can hold 10 wireless discussion units and 2 charging units

Order number **DCN-FCWD10**

Represented by:

Americas:

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com