



BOSCH
Invented for life

LBC 1259/00 Universal Floorstand



- ▶ Multi-purpose, lightweight aluminum stand
- ▶ For mounting a loudspeaker, wireless access point or Integrus radiator
- ▶ Double-braced folding base
- ▶ Reducer flange for different mountings
- ▶ Hand-adjustable
- ▶ Carrier bag for two pieces as optional accessory

This universal floorstand provides effective mounting solutions for loudspeaker installations, a Wireless Access Point of the DCN-Wireless system, or a radiator of the Integrus digital language distribution system. They are manufactured and finished to the same high standards as all Bosch products, assuring excellent quality and guaranteed compatibility throughout the range. The LBC 1259/00 is suited to a wide range of applications where a secure yet transportable mounting solution is required.

Functions

Adjustable and safe

The LBC 1259/00 floorstand is hand-adjustable using a spring-loaded locking screw for heights between 1.4 and 2.2 m (4.6 and 7.2 ft). An extra safety bolt on the support can be tightened to ensure the stand remains extended.

This lightweight stand has a double-braced folding base for extra strength, and a wide leg span to ensure stability.

Adaptable

The floorstand is standard supplied with a 36 mm (1.42 in) reducer flange with an M10 x 12 threaded pin to mount different sized equipment, and with an M10 knob to fix the Wireless Access Point mounting bracket.

Accessories

For storage and ease of transport, a carrier bag is available with two inside compartments with separate zippers for holding two universal floorstands (LBC 1259/00). The bag, with Bosch logo, is made from sturdy black weather-proof nylon. Two handles are fitted for carrying the bag by hand or over the shoulder.



LM1-CB Carrier Bag (optional)

Installation/Configuration Notes



LBC 1259/00 with DCN Wireless Access Point, LBB 451x/00 Infra-red Radiator and XLA 3200 Line Array Loudspeaker

Length

| | |
|----------|-------------------------------|
| Color | Black with light grey handles |
| Material | Nylon |

Ordering Information

| | |
|---|-------------------|
| LBC 1259/00 Universal Floorstand | LBC1259/00 |
| Lightweight aluminum construction, foldable, M10 x 12 reducer flange. | |

Accessories

| | |
|---|---------------|
| LM1-CB Carrier Bag for two floorstands | LM1-CB |
| LBC 1259/00 | |

Parts Included

| Quantity | Component |
|----------|---|
| 1 | LBC 1259/00 Universal Floorstand |
| 1 | 36 mm (1.42 in) reducer flange with (M10 x 12) threaded pin |
| 1 | M10 securing knob for WAP mounting bracket |

Technical Specifications

Mechanical

Length

| | |
|----------|--------------------------------|
| standing | 1.375 to 2.185 m (54 to 86 in) |
| folded | 1.20 m (47 in) |

Width

| | |
|---------------|------------------|
| legs extended | 980 mm (38.6 in) |
| legs folded | 130 mm (5.1 in) |

| | |
|---------------|------------------|
| Weight | 3.5 kg (7.7 lb) |
| Max. load | 50 kg (110.2 lb) |
| Material | Aluminum |
| Tube diameter | 36 mm (1.42 in) |
| Thread | 1/2" Whitworth |

Carrier bag accessory

| | |
|--------------------|-------------------------------|
| Dimensions (L x D) | 1.25 m x 27 mm (49 x 1.06 in) |
| Weight | 750 g (1.65 lb) |

Americas:
 Bosch Security Systems, Inc.
 130 Perinton Parkway
 Fairport, New York, 14450, USA
 Phone: +1 800 289 0096
 Fax: +1 585 223 9180
 security.sales@us.bosch.com
 www.boschsecurity.us

Europe, Middle East, Africa:
 Bosch Security Systems B.V.
 P.O. Box 80002
 5600 JB Eindhoven, The Netherlands
 Phone: + 31 40 2577 284
 Fax: +31 40 2577 330
 emea.securitysystems@bosch.com
 www.boschsecurity.com

Asia-Pacific:
 Bosch Security Systems Pte Ltd
 38C Jalan Pemimpin
 Singapore 577180
 Phone: +65 6319 3450
 Fax: +65 6319 3499
 apr.securitysystems@bosch.com
 www.boschsecurity.com

Represented by